

GX32 VoIP Gateway



GX series is designed to enhance your voice quality and powerful IP/PSTN network. Kylink has over 35 years manufacturing experience in Taiwan for telecommunication products. GX32 is the latest generation Gateway, can definitely bring your traditional PSTN into VoIP communication seamlessly.

Interface

1. Ethernet port: (1) Two 10/100Mbps Fast Ethernet port (1WAN + 1LAN).
(2) Support DHCP / PPPoE / Static IP .
(3) WEB console for setting and management.
2. FXO/FXS Port: (1) Reverse Polarity (option) (FXS, FXO)
(2) PFT (Power Failure Transfer) and FXO-FXS By-Pass °



GX8
(4FXS/4FXO/4VoIP)



GX16
(8FXS/8FXO/8VoIP)

Character

Power: AC 110V/220V Input adapter
Dimension: 304mm x 203mm x 51mm (W x L x H)
Weight : 1.8 Kg net weight
Temperature: (A) Operation : -10°C ~ +65°C
(B) Store : -20°C ~ + 70°C
Humidity: 0 ~ 95%

Significant features

- BYWAY: Automatic routing when priority server fail or routing to FXO.
- Multi-Registration (maximum 8 servers)
- Dynamic status inquiry
- Busy tone detect and release
- Phone number inquiry
- Flexible numbering plan
- Hotline
- Enquiry for internal log and external log server
- Inbuilt Router
- QOS
- APS (Auto Provision)
- CLI (DTMF/FSK)
- Lightning protection
- Firewall

