# SkyLink 2300T

SKYLINK 2300T GPS device is built-in a 7" touch screen LCD and a 3.5G wireless module. The driver can easily via internet access terminal to have the real-time guide and obtain internet information. It is especially appropriate for taxi, logistic and Bus Company to wisely and precisely handle the vehicles.

## SKYLINK 2300T

SKYLINK 2300T sending vehicle's essential data to vehicle monitor center via proven and stable GSM/GPRS communication network. It is fit for logistic and truck company to trace consignment and dispatch vehicles efficiently. The supervisor and vehicle drivers can have a real-time communication via control center. The GPRS transmit duration can be set from 5 to 30 seconds for saving traffic of data package and GPRS expenses.

SKYLINK2300T is available for co-working with navigator AP software to enhance the device to have features of navigation. Drivers can use built-in 7" touch screen LCD plan a real-time route; also can get through the 3.5G wireless internet to browse information on internet.

## Specfications

| | |
|---|---|
| O.S | Microsoft Windows CE |
| CPU | Samsung ARM11 667MHz |
| Inbuilt Memory | a. Mobile DDR SDRAM  256M<br>b. SLC NAND Flash  256M |
| USB | · USB Host Port x 2, support Flash driver, USB printer, SIM card reader, Barcode scanner.<br><br>· USB HS OTG Port x 1 for P.C. |
| Serial Port | Serial Port x 2, for mileage meter, fuel sensor...and customization. |
| Audio Interface | Adopt AC97 Chipset, Inbuilt Microphone/Speaker, MP3/WMA/WAV playable. |
| SD Card | Micro SD (2G Bytes) |
| GPS | Inbuilt GPS Module. |
| SIM | 3G WCDMA/UMTS      Dual-band: 900/2100 MHz<br>2G GSM/GPRS/EDGE   Quad-band: 850/900/1800/1900 MHz |
| Screen | 7" TFT-LCD touch screen, resolution 800 x 480 24 bits full color. |
| Graphics | 3D Graphics Accelerator,support Mpeg4/H.263/H.264 coder decoder, MFC/JPEG CODEC |
| Weight/Dimension | 570g, 197 x 132 x 38mm (L x W x H) |

**KYLINK COMMUNICATIONS CORP.**